




**RECHARGEABLE PORTABLE LED FLOOD LIGHT**

- < Model: GD-F024-1T
- < Epistar COB LED, 110lm/W.
- < Original driver ensures a very long life span
- < Superior Aluminum with high thermal conductivity for efficient heat dissipation.
- < 4.0mm lead-free transparent toughened glass.
- < Waterproof rating: IP65, Insulation class: II.

POWER SUPPLY 

Model	GD-F024-1T
Power Consumption	10w
Shell Color	Black Yellow
LED Chip	Taiwan Epistar 1734
Battery Type	7.4V,4.4Ah Lithium battery
Charging Time	About 4 hours
Working Time	About 3-12 hours
Light Source	High power integrated LED
LM/W	110lm/w
COB LEDs	10w × 1
LED Luminous Flux	780lm
Color Temperature	3000-6000K
Color Rendering Index	Ra>70
Humidity	0~90%
Beam Angle	120°
Housing Material	PC & Aluminum
Adapter	Input 100-240V AC 50/60Hz
	Output 12V DC 1000mA
Operating Temperature	-20°C to 55°C
Storage Temperature	0°C to 40°C
Power Factor (PF)	>92
IP Level	IP65
Life Span	40,000 hours
Weight	1.15kg
Unit Dimension	165*157*227mm
Packing Size	213*157.5*167mm
Packing Quantity	12 pcs/ctn
Carton Meas	495*445*360mm
Warranty	3 years
Certification	CE,RoHS

**SHEN ZHEN GOOD LIGHTING CO., LTD**

Tel:+86-755-8524 2901 Fax:+86-755-8524 2902 E-mail:Info@szgoodlighting.com Web:www.szgoodlighting.com  
 Add: 14G Times Center, No.102 Zhongxin Road, Shajing Town, Bao'an District, Shenzhen, China, 518125

INSTITUTIONAL DIMENSIONS

